



**EVALUATION OF THE RED JACKET  
XLP LINE LEAK DETECTOR  
FOR HOURLY MONITORING**

**EPA EVALUATION FORMS**

**PREPARED FOR  
MARLEY PUMP COMPANY**

**DECEMBER 21, 1990**



**KEN WILCOX ASSOCIATES, 1312 S 21ST ST, BLUE SPRINGS, MO 64015**

**EVALUATION OF THE RED JACKET  
XLP LINE LEAK DETECTOR  
FOR HOURLY MONITORING**

**EPA EVALUATION FORMS**

**PREPARED FOR  
MARLEY PUMP COMPANY  
5800 FOXRIDGE DRIVE  
MISSION, KANSAS 66202**

**December 21, 1990**

## Preface

The data contained in this report were obtained from the Red Jacket XLP Line Leak Detector when operated as an Hourly Monitor. The test results are based on data collected using the EPA protocol "Standard Test Procedures for Evaluating Leak Detection Methods: "Pipeline Leak detection Systems", EPA/530/UST-90/010, September, 1990. The work was conducted at the Leak Detection Test Center which is operated by Ken Wilcox Associates. Questions should be directed to Mr. Wayne Hill, Marley Pump Company at (913) 831-5700.

H. Kendall Wilcox, PhD

KEN WILCOX ASSOCIATES

*H. Kendall Wilcox*

December 21, 1991

**Results of the Performance Evaluation  
Conducted According to EPA Test Procedures**

**Pipeline Leak Detection System  
Used as an  
*Hourly Test***

This form summarizes the results of an evaluation to determine whether the pipeline leak detection system named below and described in Attachment 1 complies with federal regulations for conducting an hourly test. The evaluation was conducted according to the United States Environmental Protection Agency's (EPA's) evaluation procedure, specified in *Standard Test Procedures for Evaluating Leak Detection Methods: Pipeline Leak Detection Systems*. The full evaluation report includes seven attachments.

Tank system owners who use this pipeline leak detection system should keep this form on file to show compliance with the federal regulations. Tank system owners should check with state and local agencies to make sure this form satisfies the requirements of these agencies.

---

**System Evaluated**

System Name: Red Jacket XLP

Version of System: \_\_\_\_\_

Manufacturer Name: Marley Pump Co.

5800 Foxridge Drive

(street address)

Mission, KS 66202

(city, state, zip code)

(913) 831-5700

(telephone number)

---

**Evaluation Results**

1. The performance of this system

meets or exceeds

does not meet

the federal standards established by the EPA regulation for hourly tests.

The EPA regulation for an hourly test requires that the system be capable of detecting a leak as small as 3.0 gal/h with a probability of detection ( $P_D$ ) of 95% and a probability of false alarm ( $P_{FA}$ ) of 5%.

2. The estimated  $P_{FA}$  in this evaluation is 0 % and the estimated  $P_D$  against a leak rate of 3.0 gal/h defined at a pipeline pressure of 10 psi in this evaluation is 100 %.

11. A mechanical line leak detector  
 was  
 was not  
 present in the majority of the pipeline systems used in the evaluation.
12. Please specify how much time elapsed between the delivery of product and the start of the data collection:  
 0 to 6 h  
 6 to 12 h  
 12 to 24 h  
 24 h or more

### Temperature Conditions

This system was evaluated under the range of temperature conditions specified in Table 1. The difference between the temperature of the product circulated through the pipeline for 1 h or more and the average temperature of the backfill and soil between 2 and 12 in. from the pipeline is summarized in Table 1. If Option 1, 2 or 5 was used, a more detailed summary of the product temperature conditions generated for the evaluation is presented in Attachment 4. If Option 3 or 4 was used, no artificial temperature conditions were generated.

Table 1. Summary of Temperature Conditions Used in the Evaluation

Minimum Number of Conditions Required	Number of Conditions Used*	Range of $\Delta T$ (°F)**
1	2	$\Delta T < -25$
4	8	$-25 \leq \Delta T < -15$
5	10	$-15 \leq \Delta T < -5$
5	10	$-5 \leq \Delta T < +5$
5	10	$+5 \leq \Delta T < +15$
4	8	$+15 \leq \Delta T < +25$
1	2	$\Delta T > 25$

\*This column should be filled out only if Option 1, 2, or 5 was used.

\*\* $\Delta T$  is the difference between the temperature of the product dispensed through the pipeline for over an hour prior to the conduct of a test and the average temperature of the backfill and soil surrounding the pipe.

### Data Used to Make Performance Estimates

13. The induced leak rate and the test results used to estimate the performance of this system are summarized in Attachment 5. Were any test runs removed from the data set?  
 no  
 yes
- If yes, please specify the reason and include with Attachment 5. (If more than one test was removed, specify each reason separately.)

- the waiting time between the last delivery of product to the underground storage tank and the start of data collection for the test is 0 h
- the waiting time between the last dispensing of product through the pipeline system and the start of data collection for the test is 0 h
- the total data collection time for the test is     \* h \*1/60 - 1/4 depending on temperature
- the volume of the product in the pipeline is less than twice the volume of the product in the pipeline system used in the evaluation, unless separate written justification for testing larger pipeline systems is presented by the manufacturer, concurred with by the evaluator, and attached to this evaluation as Attachment 8
- please give any other limitations specified by the vendor or determined during the evaluation: None

*Disclaimer: This test procedure only addresses the issue of the system's ability to detect leaks in pipelines. It does not test the equipment for safety hazards or assess the operational functionality, reliability or maintainability of the equipment.*

### Attachments

Attachment 1 - Description of the System Evaluated

Attachment 2 - Summary of the Performance of the System Evaluated

Attachment 3 - Summary of the Configuration of the Pipeline System(s) Used in the Evaluation

Attachment 4 - Data Sheet Summarizing Product Temperature Conditions Used in the Evaluation

Attachment 5 - Data Sheet Summarizing the Test Results and the Leak Rates Used in the Evaluation

Attachment 6 - Data Sheet Summarizing the Test Results and the Trapped Vapor Tests

Attachment 7 - Data Sheet Summarizing the Test Results Used to Check the Relationship Supplied by the Manufacturer for Combining the Signal and Noise

### Certification of Results

I certify that the pipeline leak detection system was operated according to the vendor's instructions. I also certify that the evaluation was performed according to the procedure specified by the EPA and that the results presented above are those obtained during the evaluation.

H. Kendall Wilcox  
(name of person performing evaluation)

H. Kendall Wilcox  
(signature)

12/21/90  
(date)

816-229-0860  
(telephone number)

Ken Wilcox Associates  
(organization performing evaluation)

1312 south 21st Street  
(street address)

Blue Springs, MO 64015  
(city, state, zip)

## Attachment 1

### Description

#### Pipeline Leak Detection System

This form provides supporting information on the operating principles of the leak detection system or on how the equipment works. This form is to be filled out by the evaluating organization with assistance from the manufacturer before the start of the evaluation.

Describe the important features of the system as indicated below. A detailed description is not required, nor is it necessary to reveal proprietary features of the system.

To minimize the time required to complete this form, the most frequently expected answers to the questions have been provided. For those answers that are dependent on site conditions, please give answers that apply in "typical" conditions. Please write in any additional information about the system that you believe is important.

Check all appropriate boxes for each question. Check more than one box per question if it applies. If 'Other' is checked, please complete the space provided to specify or briefly describe the matter. If necessary, use all the white space next to a question to complete a description.

---

**System Name and Version:** Red Jacket XLP

**Date:** Dec. 20, 1990

---

#### Applicability of the System

1. With what products can this system be used? (Check all applicable responses.)

gasoline

diesel

aviation fuel

fuel oil #4

fuel oil #6

solvent (as specified by manufacturer)

waste oil

other (specify) \_\_\_\_\_

2. What types of pipelines can be tested? (Check all applicable responses.)

fiberglass

steel

other (specify) Rigid piping w/bulk modulus greater than 20,000psi

3. Can this leak detection system be used to test double-wall pipeline systems?

yes

no

inner pipe only

18. Can a test be performed with trapped vapor in the pipeline?

yes  no

19. If trapped vapor is found in the pipeline, is it removed before a test is performed?

yes  no

20. Are deviations from this protocol acceptable?

yes  no (not possible)

If yes, briefly specify: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

21. Are elements of the test procedure determined by on-site testing personnel?

yes  no

If yes, which ones? (Check all applicable responses.)

waiting period between filling the tank and the beginning of data collection for the test

length of test

determination of the presence of vapor pockets

determination of "outlier" (or anomalous) data that may be discarded

other (Describe briefly.) \_\_\_\_\_

---

### Data Acquisition

22. How are the test data acquired and recorded?

manually  not applicable

by strip chart

by computer

by microprocessor

23. Certain calculations are necessary to reduce and analyze the data. How are these calculations done?

manual calculations by the operator on site  not applicable

interactive computer program used by the operator

automatically done with a computer program

automatically done with a microprocessor

---

### Detection Criterion

24. What threshold is used to determine whether the pipeline is leaking?

2 gal/h (in the units used by the measurement system)

2 gal/h (in gal/h)



25. Is a multiple-test sequence used to determine whether the pipeline is leaking?

( ) yes (If yes, answer the three questions below)

(X) no (If no, skip the three questions below)

How many tests are conducted? \_\_\_\_\_

How many tests are required before a leak can be declared? \_\_\_\_\_

What is the time between tests? \_\_\_\_\_

(Enter 0 if the tests are conducted one after the other.)

---

### Calibration

26. How frequently are the sensor systems calibrated?

( ) never

( ) before each test

( ) weekly

( ) monthly

( ) semi-annually

(X) yearly or less frequently (minimum annual maintenance check)

**Attachment 2**  
**Summary of Performance Estimates**  
**Pipeline Leak Detection System**  
**Used as an**  
**Hourly Test**

Complete this page if the pipeline leak detection system has been evaluated as an hourly test. Please complete the first table. Completion of the last three tables is optional. (The last three tables present the performance of the system for different combinations of thresholds, probabilities of false alarm, and probabilities of detection. They are useful for comparing the performance of this system to that of other systems.)

**Performance of the Pipeline Leak Detection System as Evaluated**

Description	Leak Rate (gal/h)	$P_D$	$P_{FA}$	Threshold (gal/h)
Evaluated System	3.0	1.0	0.0	N/A
EPA Standard	3.0	0.95	0.05	N/A

**Probability of False Alarm as a Function of Threshold**

Threshold (gal/h)	Probability of False Alarm
Not determined in this evaluation	0.10
	0.075
	0.05
	0.05

**Probability of Detection as a Function of Threshold for a Leak Rate of 3.0 gal/h**

Threshold (gal/h)	Probability of Detection
Not determined in this evaluation	0.95
	0.90
	0.80
	0.50

**Smallest Leak Rate that Can Be Detected with the Specified Probability of Detection  
and Probability of False Alarm**

Leak Rate (gal/h)	Probability of Detection	Probability of False Alarm
Not determined in this evaluation	0.95	0.10
	0.95	0.075
	0.95	0.05
	0.90	0.05
	0.80	0.05
	0.50	0.05

**Attachment 3**

**Summary of the Configuration of the Pipeline System(s)  
Used in the Evaluation**

**Pipeline Leak Detection System  
Options 1, 2, and 5**

<b>Specialized Test Facility, Operational Storage Tank System, or Computer Simulation</b>	
Inside diameter of pipeline (in.)	3"
Length of pipeline (tank to dispenser) (ft)	176'
Volume of product in line during testing (gal)	64.6 gal.
Type of material (fiberglass, steel, other <sup>1</sup> )	fiberglass
Type of product in tank and pipeline (gasoline, diesel, other <sup>2</sup> )	gasoline
Was a mechanical line leak detector present? (yes or no)	yes
Was trapped vapor present? (yes or no)	yes
Bulk Modulus (B) (psi)	34,250
B/V <sub>0</sub> (psi/mil)	0.14
Storage tank capacity (gal)	560 gal

<sup>1</sup> Specify type of construction material.

<sup>2</sup> Specify type of product for each tank.

**Attachment 7 \***

**Data Sheet Summarizing the Test Results Used to Check the Relationship  
Supplied by the Manufacturer for Combining the Signal and Noise**

**Pipeline Leak Detection System  
Options 1 and 5**

<b>First Check</b>		
<b>Test No.</b>	<b>Actual Leak Rate* (gal/h)</b>	<b>Measured Leak Rate (gal/h)</b>
1		
2		
3		
4		
5		
6		

\* Recommended leak rates for monthly monitoring tests and line tightness tests: 0.0, 0.05, 0.10, 0.20, 0.30 and 0.40 gal/h. Recommended leak rates for hourly tests: 0.0, 2.0, 2.5, 3.0, 3.5, and 4.0 gal/h.

<b>Second Check</b>		
<b>Test No.</b>	<b>Actual Leak Rate* (gal/h)</b>	<b>Measured Leak Rate (gal/h)</b>
A		
B		
C		
A + B*		

\* A + B is the summation of the results of Tests A and B using the manufacturer's relationship for combining the signal and the noise.

\* Testing was conducted at both zero and leak conditions.